

# WATERPROOFING

## Product data sheet

### alwitra Primer SK-L

The alwitra Primer SK-L is a solvent based primer for use with the alwitra Evalon VSK waterproofing membrane.

#### Technical Data

<b>Base</b>	SBS rubber, solvent-containing
<b>Consistency</b>	liquid, rollable / brushable
<b>Colour</b>	red
<b>Installation Temperature</b>	min. +5 °C
<b>Drying Time</b>	approx. 15 min (after that, the roof area can be walked on)
<b>Storage Conditions</b>	dry, cool, frost-protected
<b>Shelf Life</b>	approx. 12 months

#### Application Instructions

##### Substrate conditions:

Dry, sound, clean and free from dust, grease, oil and separating agents

##### Application:

Thoroughly stir the alwitra Primer SK-L in the container (25 L / 10 L). Apply an even, thin coat to the surface with a brush or a paint roller.

##### Min. quantity of primer:

Approx. 0.2 L/m<sup>2</sup> depending on the substrate. The applied quantities will be increased for rugged and absorbent substrates.

**The primer must be completely dry before applying the EVALON® VSK**

##### Note:

alwitra Primer SK-L must be used in all applications of Evalon® VSK membrane, please contact ICB (Waterproofing) LTD Technical Support for further information.