



## Fleet Quartz Sand

**Fleet Quartz Sands are matched, low-dust and fire-dried quartz sand mixtures used as toppings.**

### MATERIAL

Fire-dried, low-dust quartz sand mix

### APPLICATION

For use as toppings in Fleet sealers to increase slip resistance.

Equally a topping can help to provide a better key under subsequent other surfacing.

### PACKAGING

- 25 kg bag in particle sizes:
- 0.10 - 0.60 mm
- 0.70 - 1.20 mm
- 1.00 - 2.00 mm

### STORAGE

Store the products in their original packaging, in a dry place and protected from moisture.

### TECHNICAL DATA

Apparent density:

0.10 - 0.60 mm approx. 1.60 g/cm<sup>3</sup>

0.70 - 1.20 mm approx. 1.50 g/cm<sup>3</sup>

1.00 - 2.00 mm approx. 1.50 g/cm<sup>3</sup>

### GENERAL INFORMATION

The above information, especially information about application of the products, is based on extensive development work as well as many years of experience and is provided to the best of our knowledge.

However, the wide variety of requirements and conditions on site mean that it is necessary for the product to be tested to ensure that it is suitable for the intended purpose. Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology or improvements to our products.