



STRATAPRIME

FAST DRYING BITUMEN PRIMER

PROFILE

ICB STRATAPRIME is a priming solution designed to deeply penetrate and seal porous surfaces to provide a base for bituminous waterproofing and flashing systems. Ideal for the sealing of metal, concrete, cement, slate, roofing fibre cement, bitumen based materials and flashing tapes.

It contains a wetting agent to enable it to be applied to 'damp' as well as dry surfaces.

ADVANTAGES

- Early resistance to rain
- Multi-use product
- Simple brush application

APPLICATION INSTRUCTIONS

- ICB STRATAPRIME may be applied to damp or dry surfaces and is suitable for application to a variety of surfaces.
- ICB STRATAPRIME is resistant to rainfall and dries rapidly
- Surfaces on to which ICB STRATAPRIME is applied must be clean and free from dirt, grease or other materials which may impair adhesion. If moss or lichen is present, this should be removed and the substrate treated with Fungicide, applied in accordance with its application instructions.
- ICB STRATAPRIME can be applied by brush to damp (not wet) or dry surfaces. The material dries quickly and is resistant to rainfall 20-30 minutes after application.
- ICB STRATAPRIME contains a flammable solvent and all normal precautions against fire must be taken during both storage and use. Keep away from sources of ignition.

TECHNICAL DATA

ICB STRATAPRIME	
COLOUR	Black
SPECIFIC GRAVITY	0.88 @ 15°C
DRYING TIME	Touch dry 30 mins, fully dry 1.5 hours
PACKAGING	5 and 25 litre Drums
FLASH POINT	38 °C
COVERAGE	Metal Surfaces 12-16m ² /L Porous Surfaces 6-8 m ² /L Lightweight concrete screeds 3.5 -5 m ² /L /asbestos cement
SHELF LIFE	24 months in tightly sealed undamaged containers
SOLIDS CONTENT	40% by weight minimum

01202 785 200

info@icbwatertight.co.uk

icbwatertight.co.uk

UK Head Office, Unit 9-11 Fleets Industrial Estate Willis Way, Poole, Dorset BH15 3SU